

SIDEWINDER™

TACTICAL FLASHLIGHT WITH ARTICULATING HEAD




Articulating 185° rotating head



to MOLLE or belt

Clip can be mounted
on either side of the light





Sidewinder, the most versatile military light in the world.

Twenty flashlights in one! Each LED features 4 levels of output intensities: Low (5%), Medium (20%), Medium-High (50%), High (100%) plus a Strobe function (100%)

- Pull and rotate locking color selector knob to attain desired color
- attain desired color
 Double click button to initiate strobe function from "Off" position
- Push and hold button for light output levels from "Off" position
- Powered by 2 "AA" batteries. Full run time chart on reverse
- Also accepts 2 "AA" lithium batteries, which allow extended operation, or extreme temperatures (-40°F - 150°F)

- Mounts to MOLLE or ACH for hands-free use
- O-ring sealed for waterproof operation. Meets MIL-STD-810F, Method 512.4
- Weight: 4.96 ounces
- Available in Coyote Tan and Marine Olive Drab
- US and foreign patents pending
- One year limited warranty

Sidewinder Light Output and 2 AA Alkaline Battery Run Time

LED	Light Output	Low 5% Intensity	Medium 20% Intensity	Medium-High 50% Intensity	High 100% Intensity	Strobe 100% Intensity
1/2 Watt White	20 Lumens	100 Hrs+	36 Hrs	14 Hrs + 1 Hr Low**	7 Hrs + 3 Hrs Low**	14 Hrs + 6 Hrs Low**
Red	630nm	100 Hrs+	70 Hrs	40 Hrs	14 Hrs + 1 Hr Low**	28 Hrs + 2 Hrs Low**
Blue	470nm	100 Hrs+	60 Hrs	36 Hrs	12 Hrs + 1 Hr Low**	24 Hrs + 2 Hrs Low**
Green/IR	520nm/880nm	100 Hrs+	60 Hrs	36 Hrs	10 Hrs + 1 Hr Low**	24 Hrs + 2 Hrs Low**

^{**}Intensity automatically shifts to low output at end of rated battery capacity to utilize maximum battery life.



Clips on MOLLE, backpack loop or belt.



Clips onto helmet with helmet mount accessory. (Helmet mount sold separately.)



1/2 watt super-bright white LED.



No other flashlight gives the range of output performance, from an entire room to covert task-lighting.

Streamlight, Inc. 30 Eagleville Road, Eagleville, PA 19403 Phone: 610.631.0600 800.523.7488 Fax: 610.631.0712 800.220.7007 www.streamlight.com © 2007 Streamlight, Inc.

STREMML

990699 5/07